Product data sheet Characteristics

CCT56P002 ARGUS standard indoor 360° - carton





Complementary

Range of product	ARGUS standard movement detector	
Range	ARGUS	
Product or component type	Movement detector	
Load type	Halogen lamp: 1000 W AC Incandescent lamp: 1000 W AC Fluorescent tube: 250 VA AC Compact fluorescent lamp: 4 x 23 W AC Capacitive: : 6 A 28 µF AC Low voltage halogen lamp with wire-wound transformer: 500 VA Low voltage halogen lamp with electronic transformer: 315 VA	
Colour tint	White	
Type of packing	Carton	
[Ue] rated operational voltage	220240 V	
Network frequency	50 Hz	
[Ue] rated operational voltage	220240 V	
Output current	10 A	
Type of setting	Time adjustment Light sensitivity adjustable	
Time delay	3 s10 min	
Light intensity adjustment	52000 lux	
Horizontal detection angle	0360 °	
Detection face	Radius: 3.9 m	
Condition of use	Indoor use only	
Material	ABS + PC matt	
Device mounting	Ceiling	
Mounting height	2.4 m	

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free
Market segment	Residential Small commercial

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1342 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------

Product Life Status : Commercialised

