

KB 26 Cable bracket 30450



Areas of application:

For the conduit laying of non-metallic sheathed cables. The KB 26 cable bracket can hold up to 26 cables (3 x 1.5 mm²).

Installation Guide:

- Drill a 6 mm Ø hole
- Insert the KB into the drill-hole
- Insert the cable/s into the gap between the wall and ceiling.
- If required up to two EC clamps, in any pipe diameter size can be attached directly to the KB

Product details:

Colour	light grey
Content box	50
Clamping range mm	200

Product benefits/properties:


Perfect and quick laying of multiple cables directly on the ceiling. Insert the KB with minimal effort, then lay the cable. The KBs own internal stress is sufficient to ensure the cable is mounted firmly even against high temperature fluctuations. Unique attachment option for the EC Euro Clip - for retrofitting of a pipe or the separate laying of different cables - without the need for drilling.

Technical data:

Material	PP, UV stabilised Temperature range: -10 °C up to +85 °C silicon-free halogen-free
----------	----------------------------------------------------------------------------------------------------

Weight per piece	10,60 g
Max. recd. load	150.4 N concrete
Breaking load	376 N (37 kg) concrete

GTIN (EAN)	 9 008439 304509
------------	--------------------------------------------------------------------------------------------------------



The KB cable brackets have been developed for the section installation of wiring harnesses.

